



Speaker type	24" forward-firing woofer, with dual 5" voice coil
Xmax	45 mm excursion each direction (90 mm linear), voice coil remaining in homogeneous magnetic field, linear and lowest distortion
Passive Active	Passive
Recommended amplifiers	1Ch DSP + 2 Amp. channels are required. Min. recommended amplifiers: 2 x 99 Vrms, 140 Vpk, 25 A; equivalent to 2500W@4Ω per channel, total 5000W with correct RMS & Peak limiting & compression settings.
Recommended ASCENDO amplifiers	DSP4-10K2
Prinziple	Sealed
SPL peak	Measurement data 134 dB @40 Hz 120 dB @20 Hz 104 dB @10 Hz
Frequency range	Measurement data (without ext. DSP) 28 Hz - 500 Hz / -3 dB 20 Hz - 500 Hz / -15 dB
Efficiency	90 dB / 1W/m
Power handling	2 x 2500 W
Impedance	Dual voice coil, 4 Ω each
Air volume displacement	9,9 L / in comparison 18" standard cinema subwoofer 1,1 L
Directivity horizontal x vertical in Deg°	360°
Input Terminal	Neutrik

Enclosure	Internally braced birch ply and MDF
Width	29,53" 750 mm
Hight	43,31" 1100 mm
Hight with feet	44,29" 1125 mm
Depth	19,69" 500 mm
Depth with plug	19,69" 500 mm
Weight	255,74 lbs 116 kg
Finish	Structural paint black
Custom colour options	Piano lacquer, colour of choice, matt or other finishes upon request
Shape customization	Upon request
Mounting	Floor standing with feet